

## CH1/HS-EATX-PSU-BK-P

4 tray	CH1/4-EATX-PSU-BK-P
6 tray	CH1/6-EATX-PSU-BK-P
8 tray	CH1/8-EATX-PSU-BK-P



### Specifications

<b>Dimensions (H x W x D)</b>	4.4cm(1.75") x 48.3cm(19") x 70cm(27.5")
<b>Max Board Size</b>	12" x 13" E-ATX/SSI EEB 3.6 compliant
<b>2.5" Drive Bays</b>	4, 6 or 8 hot swap
<b>3.5" Drive Bays</b>	None
<b>5.25" Drive Bays</b>	1 exposed (slim drive)
<b>PSU Options</b>	500W EPS or 500W, 650W 1+1 hot-swap redundant or 650W 1+1 hot swap DC redundant
<b>Fans</b>	5 x 40x56mm or 4 x 40x56mm + 1 x 40x28mm or 4 x 40x28mm hot-swap fans

- Front bezel with key lock for data security and protection
- Front access USB port
- Four, six or eight external 2.5" hot-swap HDD tray with lock supported (8 tray version shown above)
- Dedicated fan access door for hot-swap fan removal
- Five hot-swap middle fans for optimized cooling
- PCI Slot via riser card

